

Wall Mounting DS LCD Display

32", 42", 55" & 65"

Datasheet



Introduction

Latech outdoor digital signage display systems are specifically suited for use in outdoor information kiosks and digital signage applications. Widest operating temperature range in the market, lowest fluctuation in internal display temperature, highest operating humidity level design resulting into extended mean time between failures. System stability and reliability in all outdoor environments, even in the most extreme conditions.

It can embed with Android digital signage system inside, also can embed with X86 mainboard with Windows OS or Linux OS as users required.

Features:

- Ultra high brightness of 2000 nits, can be readable clearly under direct sunshine
- FHD 1920*1080 LCD Panel
- Temperature Automatically Control
- IP55 Waterproof and dustproof fuselage, which can stand all weather environment

Wall Mounting DS LCD Display

	Model	LJ-OUT32FL	LJ-OUT42FL
LED Panel	LCD Size	32" LED backlight	42" LED backlight
	Display Area	698*393mm	928*522mm
	Display Resolution	1920*1080	
	Aspect Ratio	16:9	
	Brightness	1500nits	1500nits
	Contrast	4000:1	4000:1
	Response Time	6.5ms	6.5ms
	Backlight Life Cycle	50,000hours	
	Viewing Angle	178°/178°/178°/178°	
Environment	IP Class	IP55	IP55
	Working Temperature	-20°C+50°C	
	Working Humidity	5%-95%	
Housing	Cooling System	Air Cooling (fans) System	
	Color	Black (default)	
	Housing Material	Zinc Coated Steel, 7Years Anti-corrosion warranty	
	Tempered Glass	6mm tempered glass	
Power	Standby	2W	2W
	Power Input	AC 100-240V,50/60Hz	
	Max Power Consumption	160W	200W
Size/Weight	Net Size	860*575*200mm	1100*690*200mm
	Weight	/	/
Android Solution	Processor	ARM Cortex-A9, Quad-core 1.6G	
	Storage	Default 16GB SD Card	
	Network	10/100 Mbps Fast Ethernet & WiFi 802.11b/g. 3G/4G is optional	
X86 Solution	Standard	Intel i3, 4G, 500G HDD	
	Optional	Can be customized according to user's requirement	
	Network	10/100 Mbps Fast Ethernet & WiFi 802.11b/g. 3G/4G is optional	

Wall Mounting DS LCD Display

	Model	LJ-OUT55FL	LJ-OUT65FL
LED Panel	LCD Size	55" LED backlight	65" LED backlight
	Display Area	1209*680mm	1428*803mm
	Display Resolution	1920*1080	
	Aspect Ratio	16:9	
	Brightness	2000nits	2000nits
	Contrast	4000:1	4000:1
	Response Time	6.5ms	6.5ms
	Backlight Life Cycle	50,000hours	
	Viewing Angle	178°/178°/178°/178°	
Environment	IP Class	IP55	IP55
	Working Temperature	-20°C+50°C	
	Working Humidity	5%-95%	
Housing	Cooling System	Air Cooling (fans) System	
	Color	Black (default)	
	Housing Material	Zinc Coated Steel, 7Years Anti-corrosion warranty	
	Tempered Glass	6mm tempered glass	
Power	Standby	2W	2W
	Power Input	AC 100-240V,50/60Hz	
	Max Power Consumption	380W	470W
Size/Weight	Net Size	1562*880*180mm	1668*1024*300mm
	Weight	/	/
Android Solution	Processor	ARM Cortex-A9, Quad-core 1.6G	
	Storage	Default 16GB SD Card	
	Network	10/100 Mbps Fast Ethernet & WiFi 802.11b/g. 3G/4G is optional	
X86 Solution	Standard	Intel i3, 4G, 500G HDD	
	Optional	Can be customized according to user's requirement	
	Network	10/100 Mbps Fast Ethernet & WiFi 802.11b/g. 3G/4G is optional	