



## Features:

- IP55 Outdoor Digital Signage LCD Display
- Fans cooling system
- Working Temperature: -30°C~+50°C
- Full HD 1920\*1080
- High Brightness 2000nits
- All in one Digital Signage Solution, LAN, WIFI, 3G/4G
- Remotely control from a central location
- Customized Pole Mounting Kit as requested for Customer

## Introduction

Latech Outdoor Streetlight Pole Mounting Digital Signage LCD Display, is designed for smart city streetlight pole installation for advertising purpose. The system is consisting of:

- IP55 Outdoor Digital Signage LCD Display
- Web based Digital Signage Software



	Model	LJDS55	LJDS65
<b>LED Panel</b>	LCD Size	55" LED backlight	65" LED backlight
	Display Area	1209*680mm	1428*803mm
	Display Resolution	1920*1080	
	Aspect Ratio	16:9	
	Brightness	2000nits	2000nits
	Contrast	4000:1	4000:1
	Response Time	6.5ms	6.5ms
	Backlight Life Cycle	50,000hours	
	Viewing Angle	178°/178°/178°/178°	
<b>Environment</b>	IP Class	IP55	IP55
	Working Temperature	-30℃--+50℃	
	Working Humidity	5%-95%	
<b>Housing</b>	Cooling System	Air Cooling (fans) System	
	Color	Black (default)	
	Housing Material	Zinc Coated Steel, 7Years Anti-corrosion warranty	
	Tempered Glass	6mm tempered glass	
<b>Power</b>	Standby	2W	2W
	Power Input	AC 100-240V,50/60Hz	
	Max Power Consumption	380W	470W
<b>Size/Weight</b>	Net Size	1562*880*180mm	1668*1024*300mm
	Weight	/	/
<b>Android Solution</b>	Processor	ARM Cortex-A9, Quad-core 1.6G	
	Storage	Default 16GB SD Card	
	Network	10/100 Mbps Fast Ethernet & WiFi 802.11b/g. 3G/4G is optional	



## DSLJ100 Management Software:

- Web-Based Interface (Using by IE browser)
- Support unlimited players
- Multiple-Corporation support
- Content Management
- Playlist Scheduling, Layout Change
- User Management, Reporting